

Arpac L.P.

High Speed Tray Wrapper Specifications

Serial Number: 6811 Model Number: 25TW-28 Delivery Date:

Customer: Arpac Stock

General:

Color: Steel-It Gray; 803521
Infeed Elev: 34 +2,-0" Discharge Elev: 34 +2,-0"
Infeed Direction: In-line
Engineer(s): Jim Cella
Salesperson:

Electrical:

Voltage: 460 VAC, 3 Phase, 60 Hz (STD)
Full Load Amperage: 35
Main Electrical Enclosure: Side: RH Location: Tunnel
48" Wide x 24" High x 10" Deep
 Operator Interface Enclosure: Side:
" Wide x " High x " Deep
 Auxiliary Enclosure: Qty: Side:

Pneumatic:

Lubricated Air
Operating Pressure: 80 psi minimum
Air Consumption: 15 SCFM

Wrapper:

10 Main Frame: std
 01 Seal Head: std
 02 Film Feed: std
 03 Dancers: std
 05 Film Rack: std
 14 Infeed Conveyor: std Type: Mat-Top Chain
 15 (24) Seal Conveyor: std
Type: Mat-Top Chain
 64 Drive: std
 96 Pneumatics: std
 41 Guards & Doors: std

Tunnel:

Standard: Qty: 1
Type: Side Intake # of Zones: 1
Size: 32" Wide x 16" High x 60" Long
Number of Blowers per Tunnel: 1
Conveyor type: Intralox
 Bottom Air Flow; Inside height from platform:
 Separate enclosure for heater element access:
Side: Qty:
Size: " High x " Wide x " Deep
Heater Elements:
Voltage: 230 Wattage: 3000 Elements per tray: 6

Other Instructions:

1. _____
2. _____
3. _____
4. _____

Optional Features:

- Central Point Lubrication; Tubing Type: Nylon
 UL Panel CSA Panel
 Spare Parts Kit
 Low Film Alert
 By-Pass Mode
 Extra Emergency Stop
 Wash-Down Duty
 Other:

Optional Assemblies:

- 13 Casters: (Qty 4) 112278
 12 Side Smoothing Rollers:
 11 Three Way Cooling:
 11 Turbo Cooling: std
 44 Jib Crane: 101386
 06 Splice Bar:
 05 Film Cart:
 Other:
 Other:
 Other:
 Other:

Product/Film Info: Film: LDPE; 0.002" thick

#	Length	Width	Height	Speed	Film Width
1	7-20"	6-18"	4-12"		