

Arpac L.P.

Brandpack Specifications

Serial Number: 6358 Model Number: BPMPT-5152 Delivery Date: 12/30/04

General:

Color: Steel-It Gray; 803521
Infeed Elevation: 34" +2/-0" Discharge Elevation: 34"
Infeed Direction: In-line
Engineer(s): YYL
Salesperson:

Electrical:

Voltage: 230VAC, 3Phase, 60 Hz (STD)
Full Load Amperage: 120
Main Electrical Enclosure: Side: LH Location: Tunnel
70" Wide x 24" High x 10" Deep
 Operator Interface Enclosure: Side: LH
16" Wide x 20" High x 9" Deep
 Auxiliary Enclosure: Qty: 1 Side: LH

Pneumatic:

Operating Pressure: 80 psi minimum
Air Consumption: 15 SCFM

Wrapper:

10 Main Frame:
 01 Seal Head:
 02 Film Feed:
 03 Dancers:
 05 Film Rack: Side: LH,
 14 Infeed Conveyor: Type: Belt
 05 Overwrap Flight Bar:
 14 Intermediate Conveyor: Type: Belt
 15 (24) Seal Conv, 2nd Stage: Type: Belt
 64 Drive:
 96 Pneumatics:
 41 Guards & Doors:

Tunnel:

Standard: Qty: 1
Type: Upper Intake # of Zones: 1
Size: 32" Wide x 18" High x 70" Long
Number of Blowers per Tunnel: 1
Conveyor type: BELT
 Bottom Air Flow; Inside height from platform
 Separate enclosure for heater element access:

Heater Elements:

Voltage: 230 Wattage: 3000 Elements per tray: 8

Other Instructions:

1. PIN SHUTTLE
2. Vortec Cooler

Optional Features:

Central Point Lubrication; Tubing Type: Nylon
 UL Panel CSA Panel
 Spare Parts Kit
 Low Film Alert
 By-Pass Mode
 Extra Emergency Stop
 Wash-Down Duty
 Other:

Optional Assemblies:

13 Casters:
 09 Stacker:
 62 Product Guide Assembly:
 11 Three Way Cooling:
 11 Turbo Cooling:
 44 Jib Crane:
 06 Splice Bar:
 32 Hole Punch:
 71 Perforator: Type:
 04 Film Print Registration:
 02 Film Assist:
 23 Air Jet:
 Other:

Product/Film Info: Film: LDPE; 1.75 –2.5mil thick

#	Width	Length	Height	Pattern	Speed, bun/m
1	SEE LAYOUT				
3					
5					